

# MANNINGTON COMMERCIAL

## ColorScape™ and ColorSpec

<b>Construction</b>	Thermoset Rubber
<b>Height / Size</b>	18 1/8 " x 18 1/8" (460 mm x 460 mm)
<b>Profile - ColorScape</b>	Round, Square & Sculptured (Face profile height for round and square is .025" (6 mm))
<b>Profile – ColorSpec</b>	Square and Sculptured (Face profile height for square is .025" (6 mm))
<b>Overall Thickness</b>	1/8 "(3.175 mm)
<b>Pieces per Carton</b>	20 pieces
<b>Weight per Carton</b>	44 lbs. (20 kgs) per carton
<b>Static Load Limit</b>	500 psi
<b>ASTM Specification (F-1344)</b>	Class 1, Type A
<b>Flooring Radiant Panel Test (ASTM-E-648)</b>	≥ .45 watts/cm <sup>2</sup> , Passes (Class I)
<b>N.B.S. Smoke chamber Test (ASTM-E-662)</b>	<450 - Passes
<b>Installation Adhesive</b>	Mannington MR-721 Epoxy Adhesive or M-725 Polyurethane Adhesive or MR-911 One Part Acrylic Adhesive for above-grade and stairwell applications
<b>Warranty</b>	Limited 10 Year Wear Warranty. Limited 10 Year Commercial Warranty

ColorScape and ColorSpec formulations are made with our superior rubber so they retain their amazing color, resist indentations and cracking and are quiet underfoot. Built-in waxes produce a natural luster that requires no finished or stripping, lowering maintenance costs.

ColorScape and ColorSpec is not recommended in commercial areas that require static dissipation.

Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Protect all materials from the direct flow of heat from hot-air registers, radiators, or other heating fixtures and appliances.

Dirt, wetness, and improper maintenance may cause significant variation in actual performance. Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance. This product is intended solely for use indoors and is not recommended or sold for any other purpose. Use entryway systems outside each entrance to prevent dirt, sand, grit and other substance from being tracked onto floor.